



Surface Cleaning of 3M™ Ultra Durable Floor Marking Tape 971

Technical Bulletin

August 2018



3M™ Ultra Durable Floor Marking Tape 971

Thin backing provides excellent abrasion resistance and withstands lifting from forklift traffic and dragging pallets. Vibrant color is locked into the backing for long-term visibility. Easy to apply and remove.



Scotch-Brite™ Hand Pad 7447.




3M™ Doodlebug™ Pad Holders are versatile cleaning solutions.

General Cleaning Procedure

3M™ Ultra Durable Floor Marking Tape 971 can be cleaned using electric floor scrubbers and industrial solutions, or manually following the instructions below.



Manual Cleaning Instructions



- 1. Spray** 3M™ Sharpshooter™ Extra Strength No-Rinse Mark Remover directly on the surface to be cleaned or apply to surface with a cloth or sponge.
- 2. Rub** the tape surface in a circular motion using a Scotch-Brite™ Hand Pad with moderate pressure. Additional time or pressure may be needed to achieve desired results. Easier cleaning can be achieved by using a 3M™ Doodlebug™ Pad Holder with the Scotch-Brite hand pad.
- 3. Wipe** the surface clean using a clean, dry cloth or sponge.

Note: Refer to product Safety Data Sheet for specific physical properties, health hazard, first aid and precautionary information.

Surface Cleaning of 3M™ Ultra Durable Floor Marking Tape 971

Technical Information The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Selection and Use Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method or application.

Warranty, Limited Remedy and Disclaimer Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001

This Industrial Adhesives and Tapes Division product was manufactured under a quality system registered to ISO 9001:2000 standards



Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (Fax)
www.3M.com/industrial

3M, Doodlebug, Scotch-Brite and Sharpshooter are trademarks of 3M Company. ©3M 2018