

Protective One Step BW80HP

Technical Data

Date 08/2012

Product Description

Surface Protection Film BW80HP

Construction

Backing

Adhesive

Color

Polyethylene

Acrylic

Black and white

Typical Physical Properties and Performance Characteristics

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

		Test Method
Adhesion to Steel:	1.37 +/- 0.14 N/cm (350 +/- 35 gf/25mm.)	AFERA 4001 *
Total Thickness:	80 +/- 7 µm	DIN 53370
Breaking Strength:		DIN 53455
Machine Direction :	> 17 N/mm ²	
Transverse Direction:	> 11 N/mm ²	
Elongation at Break:		DIN 53455
Machine Direction:	> 200 %	
Transverse Direction:	> 350 %	

* modified for protective films

General Information

- Before application the surface must be free from oil, fat, dust and solvents. Best to apply at room temperature between >10°C and < 40°C.
- The product should be stored at room temperature (< 40°C).
- The product should be applied and removed within 12 months after date of manufacture.
- The product is resistant to:
 - moisture: good
 - oil: moderate
 - solvents: moderate
- Protective Pro BW80HP is suitable for outdoor use up to 6-9 months

Application Ideas

Protective Pro BW80HP is

- Recommended for the protection of sensitive surfaces against dirt and damage during processing, storage and mounting etc.
- Protective Pro BW80HP has a medium level of adhesion especially made to protect:
 - PVC
 - Varnished surfaces, acrylic- and synthetic resin varnish
 - Aluminum, polished
 - High grade steel, polished
 - Not suitable for copper and brass

Features	Advantages	Benefits
PE backing, black and white	resistant against moisture, oil, solvents, dirt, mechanical abrasion and	prevents surface from dirt and damage, for outdoor use
Acrylic adhesive, medium adhesion level	sticks to many high smooth or polished surfaces, cleanly removable after use	temporary surface protection cleanly removable

IMPORTANT NOTICE TO CUSTOMER:

All statements, technical information and recommendations herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of liability relating to this product are governed by the Terms of Sale subject, where applicable, to the prevailing law.

บริษัท แมททีเรียลวัน(ประเทศไทย) จำกัด
เลขผู้เสียภาษี TAX ID : 010555049853
568/4 ซอยลาดพร้าว 112 (เอี่ยมสมบูรณ์) ถนนลาดพร้าว แขวง
พลับพลา เขตวังทองหลาง กรุงเทพมหานคร 10310 ประเทศไทย

MaterialOne(Thailand) Ltd.
TAX ID : 010555049853
568/4 Soi LatPhrao 112 (Aumsomboon), Lat Phrao Rd., Plubpla,
Wangthonglang, Bangkok 10310 Thailand